



## VF - FOOT VALVES

MODEL	FITTING
VF 0.5	1/2"
VF 0.75	3/4"
VF 1	1"
VF 1.25	1 1/4"
VF 1.5	1 1/2"
VF 2	2"

- Brass foot valves, stainless steel suction filter



## VR - CHECK VALVES

MODEL	FITTINGS
VR 0.5	1/2"
VR 0.75	3/4"
VR 1	1"
VR 1.25	1 1/4"
VR 1.5	1 1/2"
VR 2	2"

- Brass check valves



## VR-FT - BALL CHECK VALVES

MODEL	FITTINGS
VR-FT 1.25 - THREADED	1 1/4"
VR-FT 1.5 - THREADED	1 1/2"
VR-FT 2 - THREADED	2"

- Check valves for submersible pumps (sewage and waste water)
- Max. working pressure 10 bar
- Min. working pressure 0.3 bar
- Working temperature -10°C ÷ +80 °C



## VR-FF - BALL CHECK VALVES

MODEL	FITTINGS
VR-FF/DN 65 - FLANGED	Ø 65 mm
VR-FF/DN 80 - FLANGED	Ø 80 mm

- Check valves for submersible pumps (sewage and waste water)
- Max. working pressure 10 bar
- Min. working pressure 0.3 bar
- Working temperature -10°C ÷ +80 °C