

ACCESSORIES FOR ELECTRIC SUBMERSIBLE PUMPS



TYPE	CODE	CABLE DIAMETER	CABLE WEIGHT	TENSILE STRENGTH
SAFETY CABLE (in polypropylene)	116310	Ø 8 mm	30 gr/m	960 kg
	116311	Ø 10 mm	45 gr/m	1425 Kg
	116312	Ø 12 mm	65 gr/m	2030 kg
	116313	Ø 14 mm	90 gr/m	2790 kg
	116314	Ø 16 mm	115 gr/m	3500 kg

- ※ Twisted cable made of UV-stabilised polypropylene yarn
- ※ Maximum available reel length: 220 metres



SAFETY CABLE (AISI 316 stainless steel)	116305	Ø 5 mm	100 gr/m	1500 kg
------------------------------------------------	--------	--------	----------	---------

- ※ 49 wire cable in AISI 316 stainless steel
- ※ Maximum available reel length: 250 metres



STRAIGHT SHACKLE WITH PIN (For 8 mm cable) (in AISI 316 stainless steel)	CODE 1160305
--------------------------------------------------------------------------------------------------	--------------



5 mm CABLE CLAMP (in AISI 316 stainless steel)	CODE 1160304
-----------------------------------------------------------------	--------------

FLOAT SWITCHES



TYPE	CODE		LENGTH
	CABLE = H07 RN-F	PVC CABLE	
0315/3	50014H	50014	3 metres
0315/5	500145H	500145	5 metres
0315/10	5001410H	5001410	10 metres

- ※ With cable **H07 RN-F**: single function (emptying), with 10 A switch
- ※ With cable **PVC**: dual function (emptying and filling), with 10 A switch



T 80/3	50014/1H	50014/1	3 metres
T 80/5	50014/5H	50014/5	5 metres
T 80/10	50014/10H	50014/10	10 metres

- ※ With **H07 RN-F** cable: single-function (emptying), double sealed float switches, with 10 A switch
- ※ With **PVC** cable: dual-function (emptying and filling), double sealed float switches, with 10 A switch



SMALL 3	50014S4	50014S3	3 metres
SMALL 5	50014S5	50014S51	5 metres

- ※ With **H07 RN-F** cable: single-function (emptying), double sealed float switches, with 10 A switch
- ※ With **PVC** cable: dual-function (emptying and filling), double sealed float switches, with 10 A switch



TYPE	CODE	CABLE	LENGTH
MAC 5	54SARGL001	PVC	10 metres

- ※ Tilting float: dual function (emptying and filling), double sealed protection chamber, with 10 A switch
- ※ Recommended for Waste Water Recovery Stations (SAR)