

ACCESSORIES



VF - FOOT VALVES

| TYPE | CODE | FITTING |
|---------|-------|---------|
| VF 0.5 | 50100 | 1/2" |
| VF 0.75 | 50101 | 3/4" |
| VF 1 | 50102 | 1" |
| VF 1.25 | 50103 | 1 1/4" |
| VF 1.5 | 50104 | 1 1/2" |
| VF 2 | 50105 | 2" |

※ Brass foot valves with stainless steel suction filter



VR - CHECK VALVES

| TYPE | CODE | FITTINGS |
|---------|-------|----------|
| VR 0.5 | 50110 | 1/2" |
| VR 0.75 | 50111 | 3/4" |
| VR 1 | 50112 | 1" |
| VR 1.25 | 50113 | 1 1/4" |
| VR 1.5 | 50114 | 1 1/2" |
| VR 2 | 50115 | 2" |

※ Brass check valves



VR-FT - BALL CHECK VALVES

| TYPE | CODE | FITTINGS |
|------------|--------|----------|
| VR-FT 1.25 | 501201 | 1 1/4" |
| VR-FT 1.5 | 501202 | 1 1/2" |
| VR-FT 2 | 501203 | 2" |

※ Check valves for submersible pumps (sewage)

※ Max. operating pressure **16 bar**

※ Min. operating pressure **0.3 bar**

※ Operating temperature 0 °C - **+80 °C**



VR-FF - BALL CHECK VALVES

| TYPE | CODE | FITTINGS |
|------------------------|--------|---------------------|
| VR-FF/DN 65 - FLANGED | 501210 | DN 65 (PN16) 2 1/2" |
| VR-FF/DN 80 - FLANGED | 501212 | DN 65 (PN16) 2 1/2" |
| VR-FF/DN 100 - FLANGED | 501214 | DN 65 (PN16) 2 1/2" |

※ Check valves for submersible pumps (sewage).

※ Max. operating pressure **16 bar**

※ Min. operating pressure **0.3 bar**

※ Operating temperature 0 °C - **+80 °C**