

0700195

COLLARE D'APPOGGIO


per saldatura nel bicchiere e sede striata da impiegare con flange libere secondo DIN 16962-12

FLANGE ADAPTOR

for socket welding with striped seat to be used for flanges (DIN 16962-12)

COLLIER DE SUPPORT

pour souder dans l'embout et siège strié à utiliser avec brides libres selon DIN 16962-12



codice / code / code	d	L(1)	Z	E	E1
0700195.072020	20	17,5	3	45	27
0700195.072525	25	19,5	3	58	33
0700195.073232	32	22	3	68	41
0700195.074040	40	23,5	3,5	78	50
0700195.075050	50	26,5	4	88	61
0700195.076363	63	30	4	102	76

0700295

BOCCHETTONE


con ghiera filettata profilo metrico per saldatura nel bicchiere con guarnizione O-ring in FPM

SOCKET UNION

with metric thread ring nut for socket welding with FPM O-ring gasket

RACCORD UNION

avec écrou fileté profil métrique pour souder dans l'embout avec joint torique en FPM



codice / code / code	d	L(1)	Z	L(2)	E
0700295.072020	20	14,5	22,5	22	53
0700295.072525	25	16	24,5	25	62
0700295.073232	32	18	26,5	26	70
0700295.074040	40	20,5	28	27	81
0700295.075050	50	24	29	31	89
0700295.076363	63	27,5	30,5	35	105

0700236

RIDUZIONE MF


per saldatura nel bicchiere, d maschio, d1 ridotto femmina

REDUCING SOCKET

for socket welding male d, female reduced d1

RÉDUCTION MF

pour souder dans l'embout, d mâle, d1 réduit femelle



codice / code / code	d	d1	L	L(1)	Z	E
0700236.072016	20	16	15	20	4	24,5
0700236.072520	25	20	16	20	5	30
0700236.073220	32	20	22	25	3	30
0700236.073225	32	25	19	25	3	35,5
0700236.074025	40	25	20	25	10	36
0700236.074032	40	32	24	18	11	45
0700236.075032	50	32	20	22	17	55
0700236.075040	50	40	28	21	9	55
0700236.076332	63	32	22	30	18	45
0700236.076340	63	40	24	28	17	56
0700236.076350	63	50	32	23,5	12	70

0700255

GOMITO a 90°


per saldatura nel bicchiere

90° ELBOW

for socket welding

COUDE à 90°

pour souder dans l'embout



codice / code / code	d	L(1)	Z	E
0700255.072020	20	14,5	13,5	30,5
0700255.072525	25	16	17	36
0700255.073232	32	18	20	43,5
0700255.074040	40	21	21,5	53,5
0700255.075050	50	24,5	27	66,5
0700255.076363	63	28	34	83

0700265

GOMITO a 45°


per saldatura nel bicchiere

45° ELBOW

for socket welding

COUDE à 45°

pour souder dans l'embout



codice / code / code	d	L(1)	Z	E
0700265.071616	16	16	3	23
0700265.072020	20	17	4	29
0700265.072525	25	16	7	34
0700265.073232	32	18	9	43
0700265.074040	40	21	11,5	53
0700265.075050	50	24	13,5	66
0700265.076363	63	28	15,5	82