

## White Polypropylene Fittings

The PPM Range of metric size push-fit fittings are produced in white polypropylene and fitted with EPDM seals.

Polypropylene has the advantage of being more chemically resistant than acetal.

### Working Pressures and Temperatures

Water 10 BAR at 20°C  
4 BAR at 60°C intermittent hot water

Minimum Temperature 1°C

Other technical information is shown on page 36.



#### EQUAL STRAIGHT CONNECTOR



PART NO.	TUBE OD
PPM0408W	8
PPM0412W	12

#### STEM ELBOW



PART NO.	STEM OD	TUBE OD
PPM220808W	8	8
PPM221212W	12	12

#### PLUG



PART NO.	STEM OD
PPM0808W	8

#### REDUCING STRAIGHT CONNECTOR



PART NO.	TUBE OD	TUBE OD
PPM201512W	15	12

#### EQUAL TEE



PART NO.	TUBE OD
PPM0208W	8
PPM0212W	12

#### DIVIDER



PART NO.	TUBE OD
PPM2312W	12

#### EQUAL ELBOW



PART NO.	TUBE OD
PPM0308W	8
PPM0312W	12

#### REDUCER



PART NO.	STEM OD	TUBE OD
PPM061512W	15	12

Adaptors to convert to Metric sizes are shown on page 19.

