

Portable - Single Post Lifts

Model	Description	Dimensions	Use With
SINGLE-POST			
67075-B	For use with 5-gallon pails containing fluids with viscosities up to 200,000 cPs. A needle valve allows the operator to control the speed at which the pump is raised and lowered.	Base: 26.593" (675.5 mm) x 27.5" 698.5 mm)	CL0443X2XXXXXXXXXX and NP322L0X0X
67075-1-B		Height: 42.921" (1090.2 mm) lowered	CL0409A9XXXXXXXXXX
67425-1	For use with 5-gallon pails containing fluids with viscosities up to 200,000 cPs. A needle valve allows the operator to control the speed at which the pump is raised and lowered.	Base: 21.844" (554.8mm) x 27-1/2" (698.5mm) Height: 41.947" (1065.4mm) lowered	Packages that include the RM051X-X-B Single Post 5 gallon ram



67075-B



640067

Stationary - Single Post Lift

Model	Description	Dimensions	Use With
SINGLE-POST			
640067	For use with 55-gallon drums. Lift is bolted to floor. Support arms attach to drum cover. Lift is used to raise drum cover and bung-mounted pump. Use when pumping grease, oil and low-viscosity fluids.	Height (lowered): 55-1/2" (1409.7 mm) Height (raised): 92" (2336.8 mm)	<ul style="list-style-type: none"> All 55-gallon bung-type pumps 651852 or 66197 drum covers



66554-2

Portable - Carts

Model	Description	Use With
66554-2	• 24" to 30" wheel spacing adjustment; has 16" tires	<ul style="list-style-type: none"> 8", 10" and 12" air motor 2-ball pumps 8" air motor Integrity 2-ball pumps
67139	<ul style="list-style-type: none"> Will clear 28" openings Unique chair design distributes pump weight and makes moving easy 12" (305 mm) pneumatic tires also enhance smooth transport 	<ul style="list-style-type: none"> 4-1/4" and 6" Integrity 2-ball pumps



67139